


## CO-sinusUPS central heating UPS

Cechy:

- Two output sockets (French type),
- Wall mounted case,
- Pure sine output wave,
- Suitable for external AGM or GEL battery,
- Automatic charger,
- LCD communication display
- AVR function



	Parametr	<b>CO-sinusUPS-400W-WM</b>
ELECTRICAL	Input voltage	230Vac 50Hz
	Input voltage range	155-290Vac 50Hz
	Output Voltage range in mains mode	200-250Vac 50Hz
	Output Voltage range in batterymode	230Vac 50Hz
	Output waveform	Pure sine wave
	Efficiency	>80%
	Output power	400W/500VA
	Overpower (max15sek.)	460W
	Transfer time	<10ms
BATTERY	Battery	External (not in set)
	Connector	M5
	Battery type	12V 26-100Ah
	Backup time	AGM, GEL, lead-acid
	Charger	13,6V/max 6A Automatic charger
ENVIRONMENT	Working temp.	0-40°C
	Humidity	20-90%
OTHER	Output sockets	2szt (French type)
	Dimmension	246 / 205 / 104mm
	Weight netto / brutto	6kg / 6,5kg (pcs)
	Packing	4pcs full box
	EAN	 5 9 0 2 1 3 5 1 2 5 8 4 7
PROTECTIONS	Overcurrent / Short circuit	Electronic fuse

## CO-sinusUPS central heating UPS

Dedicated batteries:	
MB 26-12	GLP 26-12
MB 33-12	GLP 33-12
MB 40-12	GLP 40-12
MBE 50-12	GLP 50-12
MB 65-12	GLP 65-12
MB 80-12	GLP 80-12
MB 100-12	GLP 100-12
MB 120-12	GLP 120-12
MB 150-12	GLP 150-12
MB 200-12	GLP 200-12

LCD display info:
Load level
Battery capacity level
Input voltage
Output voltage